

Technology for processing information e.g. representing print requests in networked environment a system suitable for applying this method, and a computer program element comprising a program code for applying this method

INSAI

Field of the Invention

The invention relates to technology for processing information with a system provided with at least two processing devices coupled to a network, and more particularly to processing information representing print requests.

Background of the Invention

European Patent Application No. EP 0 772 114 is directed toward a method of processing information in a system having at least two processing devices connected to a network. An order for processing informations has two parts, a job and a job ticket. A user of the system, prior to giving an order for processing information by the system, programs a job ticket so that there is selected from the system a combination of processing devices which can carry out the job settings that the user adds to an order. This takes into account the processing capabilities of the various processing devices and if required the actual available attributes thereof. The programmed job ticket can be stored by the user in a memory so that the job ticket can be used at a later stage and more than once. As soon as the user wants to give an actual order for the processing of the information to the system, for example the scanning of a set of originals, the archiving of information, the conversion of texts to word processor data (OCR), the printing of a number of reports etc., the user defines a job and combines it with a job ticket containing the required settings. This combination or order, is then fed to the system for performance.

This method has one important disadvantage. Since the user cannot give the actual order until a job ticket has been programmed, there is the risk that at the time that this order is given the selected processing device or devices are no longer suitable for carrying out the settings associated with the job.

For example, it is possible that a processing device is temporarily unavailable because another user is in the meantime using this device for a very extensive job. Furthermore, a specific processing device may in the meantime have been replaced by another type with fewer capabilities. In the case of printing devices in particular, it

The consequence of this is that the user who defines the job and transmits it to the system is assuming that the system really will perform his job, while that probably will not happen (for example because a selected device has broken down), will happen much later (for example because a selected device is temporarily unavailable) or will happen only partly (because a specific processing capability of the device is not available).

15 The invention, in part, provides a method wherein, after the job has been defined, it is clear to the user whether a selected processing device is suitable for performing the job. For this purpose, a method according to the invention comprises the following steps: a job for processing information from a user of the system, automatically checking whether processing devices belonging to a predetermined set selected from at least two
20 processing devices are suitable for performing the job, presenting an indication for each processing device of the set to the user (via presentation means) of whether the same is suitable for performing the job, receiving a selection of a processing device belonging to the set, and transmitting at least a part of the job to the selected processing device. Thus with the method according to the invention, a job is first defined completely with all the
25 required settings, and a check is made for a predetermined set of devices automatically, i.e. by the system, as to what processing devices, whether or not in combination, are suitable for performing the job. In this case it is possible to check not only whether the processing devices have the required capabilities, but also whether these capabilities are available at the time the job is defined. Furthermore, the set of processing devices is
30 presented to the user via presentation means, for example via a monitor screen or some other means generating signals which are perceptible to the user either visually, audibly, or in some other way, it being indicated for each of said devices whether the same is suitable for performing this job. On the basis of this indication, a device is selected and the job is passed to the selected device. It is also possible to split the order and transmit

a part of the job to a first device and another part to a second device so that the job can be performed more quickly.

An important supplementary advantage of the method according to the invention is that even the processing devices which are not suitable for performing the job at the time the job is defined are presented to the user. By giving the user a complete overview of both the suitable and the unsuitable processing devices, it is possible to obtain an open interaction between the user and the system. If, for example, a device that the user prefers, e.g., because it is situated at a location close to his workplace at the time, appears to be unsuitable, the user can adapt his job, for example by omitting a specific setting, so that the device which he prefers can be made suitable for performing the job. An interaction of this kind is made much easier by presenting all the processing devices belonging to the set, so that the method can give a considerable saving in time for the user.

In one embodiment of the invention, the processing devices are printing devices, for example printers, plotters and other devices which can print receiving media with image-forming materials. Particularly in the case of this type of processing device, the above-mentioned problem is present because many processing capabilities of such devices are dependent on the presence of processing materials such as receiving media, image-forming materials such as toners or inks, other auxiliary materials such as staples, covers, binding edges, glue, and so on. In addition, devices of this kind are relatively frequently subject to malfunctioning, so that a device can suddenly become unavailable for a relatively long period.

In a further embodiment of the invention, the presentation means indicates, in the event of a processing device being unsuitable for performing the order, what the reason for this is. In this way, the user is kept informed as to why a specific processing device is unsuitable. This is an important aid to the user in his dealings with the system. If the user knows why a specific device, for example the device which he normally particularly prefers, is not suitable for performing the job, he can check or determine: whether he wishes to have the job performed in adapted form by this device which in principle is unsuitable (for example by omitting a specific setting); whether the device is simply unavailable for a short time (for example the paper has to be refilled), so that his job will not be immediately performed but will be so in the very near future, if he nevertheless selects this device which in principle is unsuitable; or whether the device is unavailable for a relatively long time (for example the device is no longer in operation). In this way the user thus knows beforehand what disadvantage will occur in performing the job if he

5 Indicating the reason why a processing device is not suitable for performing a job,
can also be favourably utilised in an alternative method according to the invention in
which the system comprises one processing device. The user then knows why that
device is not suitable and he can either adapt his job, for example have it carried out to a
limited degree, or search for an alternative processing device belonging to another
10 system.

In another embodiment according to the invention, a part of the job is presented to the user, which part preferably contains one or more settings of the job. This has the advantage that the user can immediately take note of the job that he defines and has an overview of the job defined by him. Preferably, this part of the job is presented to the user via the presentation means simultaneously with the set of processing devices. In the event that the presentation means comprises a monitor screen, then in one embodiment of the method according to the invention the settings of the job are displayed in a first window and a list of processing devices belonging to the set is displayed in a second window next to the first. The user then sees at a glance which devices are suitable or unsuitable for performing the job defined by him. By allocating an unsuitable device, for example, it is then possible immediately to indicate in the first window which of the settings will not be carried out if this unsuitable device is selected for performing the job.

4

via a monitor screen, the selected device can be marked, for example by shading the background of the code by which this device is represented. In this way it is clear to the user which of the processing devices has been selected at that time for performing the job. In a further embodiment, the job is not transmitted to this selected processing device
5 until after confirmation of that selection. In this way the user always still has the possibility of changing a previous selection if that appears favourable. Preferably, the selection is confirmed by the user himself.

In one embodiment of the method according to the invention, in the first instance, a processing device is selected by the system itself on the basis of one or more
10 predetermined criteria, whereafter the user has the possibility of changing this selection. In this way the user is not compelled to select a device himself for each order but the system makes a default selection. The user still retains complete control of this because on the one hand he can input the criteria on the basis of which the system selects a device (examples of criteria are a processing property of the device, such as quality, cost
15 price and speed, distance between the device and the user or workstation, device availability, personal preference of the user, and so on) and on the other hand he can always change a default selection before he confirms the selection.

In yet another embodiment according to the invention, the presentation means separately indicates whether at least one processing device belonging to the set is
20 suitable for performing the job. This can be shown, for example, via a master symbol on the monitor screen. In this way the user is immediately informed whether his job can at least be performed as defined by him. If, for example, only one device is suitable, the above-mentioned default selection would automatically be able to relate to that device.

A system suitable for performing the method according to the invention comprises
25 coupled to a network: at least two processing devices, defining means for defining an order for processing information, research means for checking whether processing devices belonging to a predetermined set selected from the at least two processing devices are suitable for performing the defined job, presentation means for presenting the processing devices of the set, it being indicated for each processing device whether the
30 same is suitable for performing the defined job, and finally selection means for selecting a processing device.

The invention also relates to a computer program element, i.e. any medium
suitable for carrying data, for example a floppy disk, CD ROM, DVD, minidisc, network
etc., comprising a computer program code for performing the method according to the
35 invention on an information processing system.

Advantages of the present invention will become more apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

Brief Description of the Drawings

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus do not limit the present invention.

Fig. 1 is a diagram showing an information processing system suitable for applying the method according to the invention.

Fig. 2 is a flow chart again suitable for a research module belonging to the system according to the invention.

Fig. 3, which comprises Figs. 3A, 3B, 3C, 3D and 3E, shows how the method is presented to the system user according to the invention.

Detailed Description of Preferred Embodiments

Fig. 1

Fig. 1 is a diagram of an information processing system 1 according to the invention. In this preferred embodiment, the user 2, in this case a person, has interaction with the system via a display unit 3, in this case a monitor screen, and a user interface 4, more particularly a keyboard in combination with a mouse. Monitor screen 3 and the user interface 4 together form a workstation for the user.

This workstation is coupled to a server 5, including a central control module 6 for controlling the information flows within the system, a memory 7 for the storage of data, a research module 8 operable to check whether processing devices belonging to the system are suitable for performing a specific job, a define module 9 operable to define a job for the processing of information, a select module 10 for selecting a processing device, and a point module 11 for allocating a processing device. It is not essential for the system that each of these modules should form part of the server 5. It is also possible that at least some of the modules form part of the workstation or that the modules are distributed over a plurality of servers and/or workstations.

The method according to the invention can be performed on known server technology. It is only necessary to control this known server in the correct manner, i.e., according to the invention. For this purpose, the server can be provided with the correct computer program code ("software"), which enables the system to perform the method according to the invention. This software can be installed on the server via a computer program element, in this case a floppy disk 15 or a set of data on a network loaded into the server via a network connection 16.

If a user 2 wishes to print a data file he defines from the workstation an order for the printing of this information. In addition to the actual data file, this order comprises one or more settings for the printing of the file, more particularly the paper format, the paper orientation, colour or grey scale appearance, simplex or duplex printing, stapling, and so on. The system 1 offers the user a number of basic settings via the monitor screen 3, and these basic settings can be changed by the user via the user interface 4.

The control module 6 then actuates research module 8. The control module 6 communicates to the research module 8 what order has been stored in the memory, particularly the associated settings. The research module 8 then checks which of the printing devices 12, 13 and 14 is suitable for performing the order. In this preferred embodiment, the research module 8 checks not only whether the printing devices 12, 13 and 14 have the printing capabilities appropriate to the job, but also whether these capabilities are available. The result of this research is stored by the control module 6 in the memory 7 and is directly presented to the user via the monitor screen 3. A second window can be shown on this screen with a list of the printing devices, or at least codes

5 In this embodiment, there is an automatic indication whether each printing device is on standby, i.e. available for performing print jobs generally. If that is not the case, for example because there is a paper jam, or because the printing device has broken down, the reason for this is indicated.

If the user, for example, indicates a printing device which is not suitable for performing the job, because the associated printing device cannot accept one or more of the settings, control module 6 indicates, in the window in which the job settings are displayed, what the settings are that the associated printing device cannot accept, for example by marking them with a red icon.

In this preferred embodiment, the system comprises a selection module 10 with
35 which a printing device can be selected. This selection module 10 selects a default

5
10

15

20

25

30

35

Fig. 2

Fig. 2 is a flow chart suitable for the research module 8 belonging to the system. In this embodiment, the research module 8 continuously checks whether each of the printing devices is suitable for performing a job. If the user has not yet defined any concrete job, a check is made whether each of the printing devices can perform a standard job stored in the memory. This standard job comprises a text file for printing and the basic settings referred to in the description of Fig. 1. As soon as the user introduces a job via the define module 9, a check is made whether the printing devices 12, 13 and 14 are suitable for performing the input job so that the user is immediately informed of the capabilities that the system offers him for performing his job.

To carry out the check, the first printing device of the set of printing devices for checking is converted in step 201 to the current printing device, i.e. the device for checking in this partial check. In step 202 a check is then made whether this printing device comes within reach of the system. If not, for example because this printing device is not coupled to the network, the value "error" is assigned to the status. This status is stored in memory 7 via the control module 6. If the printing device is within the system reach, then the status of the device is first retrieved in step 203. In this embodiment, this status comprises all the information relating to the capabilities of the device and its availability with respect to the job. If no answer comes in step 204, then the printing device cannot be actuated and the research module assigns the value "error" to the status in step 206. If an answer does arrive, this is stored as status in the memory 7 via the control module 6. In step 207 a check is then made whether the printing device checked is the last printing device of the set being checked. If not, then in step 209 the next printing device becomes the current printing device to be checked. If so, the first printing device becomes the printing device for checking. The research then continues with step 202.

In this way the printing devices are continuously checked as to their suitability. After all the devices have been checked for suitability, it is possible to start a new check only if a change occurs in the job (for example a change of a setting) or in one of the printing devices themselves (e.g. the paper, toner, ink, staples or some other consumable has been used up, there is a paper jam, the printing device is switched off, and so on). Since in this way the server 5 is required to start a subsequent check only when a specific event occurs, it is subjected to much less loading and the consequence of a change

affecting the performance of a job defined by the user can be presented by the system to said user more quickly.

Fig. 3

Fig. 3 again is fomred of Figs. 3A, 3B, 3C, 3D and 3E. And it shows how the method is presented to the system user. As soon as the user, for example of a word processor such as Microsoft Word, decides to have a file printed, he selects the option "File/Print" in the menu of this word processor as offered via the monitor screen 3. This is illustrated in Fig. 3A by the dark or highlighted bar in the selection menu 300. As soon as this option has been selected, the print dialogue window appears on the screen as shown in Fig. 3B. In Fig. 3B, elementary settings such as the required number of copies (in the "Copies" sub-window) and the pages for printing (in the "Page Range" sub-window) can be set in this window. If the user now selects "OK" the order transmitted to the default printing device is the file for printing with standard settings (e.g.: A4 format, portrait orientation, standard paper, simplex, no staple, black and white, 300 dpi resolution, 100% scale). In that case, however, the user does not know whether the job can be performed immediately, what settings cannot be accepted, and so on. By selecting the "Properties" button 302 in the "Printer" sub-window, the dialog window 304 appears as shown in Fig. 3C.

In Fig. 3C, the left-hand box 306 displays the settings of the job, in this case the default settings: A4 format, portrait orientation, standard paper, one copy, simplex, no staple, black and white, 300 dpi resolution, scale 100%. The right-hand box 308 displays the list with printing devices belonging to the system ("HP Laserjet 5 Si to HP Laserjet 4M Plus), their location (3G09 to 3L07) and their current status. The term "OK" denotes that the relevant printing device is available, "error" indicates that the printing device is not available. Also, in the case of the dark or highlighted "HP Laserjet" printing device, a warning is given that paper tray 3 is empty. Finally, under "Display" column, extra information of importance to the user can be given for each printing device. One of the printing devices, namely "HP Laserjet" is marked by the colours of the background (dark or highlighted) around the code because this is the default printing device.

In Fig. 3C, a coloured round icon 310 indicates for each printing device whether the same is suitable for performing the job. In this embodiment, three colours are used: a green icon (half-closed icon) 312 means that the relevant printing device can perform the job as defined at that time, a yellow icon (open icon) 314 means that the printing device does have the correct properties for performing the job but at the moment they are not

00878967 061301

Sub
B7

(all) available, while finally a red icon (closed icon) 316 (not shown in Fig. 3C but see Fig. 3D) means that the relevant printing device does not have the correct properties for performing the job as defined. If the user selects the "Print" button 318 then that confirms the selection made by the system. In response to this, the system transmits the job to the default printing device "HP Laserjet", which according to the associated green icon is suitable for performing the job as defined.

If, however, the user wants a staple to connect the printed receiving materials, he can change the standard setting 320 from "Staple: False" to "Staple: True" before confirming the selection. This is shown in Fig. 3D. As a result of this change, the research module 8 will re-check whether the printing devices are suitable for performing the job. It now appears that only the printing device Océ 3165 has a green icon 312. If the user were now to select the "Print" option, the job would nevertheless be given to the default printer HP Laserjet, but this will perform the job without providing the receiving materials with a staple. The user, however, can also alter the selection by selecting the printing device Océ 3165, for example via the mouse, and then confirming this new selection by selecting the "Print" button 318. As a result the job is performed as defined.

By indicating in the right-hand window 308, for example via the mouse, a printing device which is not suitable for performing the job, the left-hand window 306 will indicate why this printing device is not suitable. This is shown in Fig. 3E.

In Fig. 3E, the user has allocated the default printing device HP Laserjet, which is shown in the window by the open frame 322 around this printing device. As a result, the round icon 324 in front of the "Staple" option 320 turns red. It is now clear to the user why this printing device is not suitable. He can then decide whether he nevertheless wants the order carried out by the default printing device, with the omission of a staple, or he can choose a printing device which is suitable.

Under the left-hand window 306 to the right of the centre a tick or checked box 326 is indicated to show the user that at least one device is suitable for performing the job. This is an advantage when there is a long list of devices which cannot all fit in the right-hand window 308.

In an alternative embodiment of the method according to the invention, use is made of soft settings. This means that a user in addition to the option "Setting x: no" and "Setting x: yes" has the opportunity of a less hard choice, for example "Jobsetting x: Don't care". This can if required be extended to settings such as "Jobsetting x: On_Nice" or "Jobsetting x: Off_Nice". By making use of such settings, a device which for example cannot carry out duplex printing is not considered unsuitable if the user has selected the

setting "Duplex: Don't care" or "Duplex: On_Nice". Via the display unit 3 means the user can be kept informed of such "less" suitability, for example by giving the green icon a red frame (not depicted). In the selection of a default device it would also be possible to allow for this outcome.

5 It should be clear that it is possible not only to show that a specific setting cannot be carried out by an allocated printing device, but that also other causes of "non-suitability" can be presented to the user in one way or another. The causes of this and how they are presented to the user do not form part of the present invention. The invention can also be expanded in obvious manner to the man skilled in the art, by
10 supplementary means such as "Queue monitoring", "Job-feedback", "Time-till-completion" and "Re-routing", which are adequately known from the prior art.

 The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are
15 intended to be included within the scope of the following claims.